

Parametry motoru se zabudovanou brzdou pro hlavní zvedání, kladkostrojů

- 2m podle normy FEM 9.511/M5, ISO 4601/400V/50Hz

Typ	Qn 2/1 /kg/	Normální rychlost				Dvojitá rychlost			
		Normální rychlost		Micro rychlost		Normální rychlost		Micro rychlost	
		Ph/kW/	I H / A/	Ph/kW/	I H / A/	Ph/kW/	I H / A/	Ph/kW/	I H / A/
WAT15	1000	1.5	5.8						
WAT25	2000	3.0	9.0			0.75/3.0	6.5/7.5	0.75/4.5	6.5/9.5
WAT35	3200	4.5	12.5						
WAT45	5000	8.0	20.0			1.7/8.0	15/18	1.7/12.5	15/23
WAT55	8000	13.0	26.0	20.0	38.0				
WAT65	12500	13.0	26.0	20.0	38.0				

Parametry motoru se zabudovanou brzdou pro elektrický jednopojzdový mechanismus pro kladkostroje - 400V,50Hz

Qn /kg/		Rychlost pojezdu			
2/1	4/1	20 m/min			
		H<13m npu 2/1 H=6 m npu 4/1		H>13m npu 2/1 H> 6 m	
		Ph /kW/	Ih /A/	Ph /kW/	Ih /A/
1000		0.12	0.75	2x0.12	2x0.75
	2000	0.25	1.1	2x0.12	2x0.75
2000		0.25	1.1	2x0.25	2x1.1
3200		0.25	1.1	2x0.25	2x1.1
	4000	0.25	1.1	2x0.25	2x1.1
5000		0.55	2.4	2x0.25	2x1.1
	6300	0.55	2.4	2x0.25	2x1.1
8000		2x0.55	2x2.4	2x0.55	2x2.4
	10000	2x0.55	2x2.4	2x0.55	2x2.4