

Technické a elektrické parametre motorov typu KG

Výkon	Typ	Otáčky	Napätie	Pracovný cyklus		Prúd	Rozbeho vý moment v>	Rozbeho vý moment CQ	Váha
				CD	SF				
kw		min'	v	%	sw/h	A	Nm	Mm	kg
0,75	KG 1605D6	910	400/230	40	240	3,3/5,7	16,4	10,8	35
1,5	KG 1608D6 KG II 1608-6	910	400/230	40	240	5,8/10,0	25,0	23,5	40 36
3,0	KG 2008D6	920	400/230	40	240	11,0/19,0	60,5	49	65
4,5	KG2011D6 KG II 2011 D6	920	400/230	40	240	15/26	78,0	78	70
8,0	KG 2412-6	920	400/230	40	240	24,5/42,5	132	105	100
12,5	KG 2714-6	920	400/230	40	240	36,0/62,0	200	165	155
1,1	KG 1605D4	1360	400/230	40	240	3,6/6,2	15	18	35
2,3	KG 1608D4	1300	400/230	40	240	6,0/10,5	26	28	40
4,5	KG 2008D4	1400	400/230	40	240	12,0/1,0	60	78	65
7,5	KG I2012-4	1380	400/230	40	240	17,0/9,5	105	100	75
12,0	KG I2714-4	1430	400/230	40	240	28,0/48,5	180	130	140
15,5	KG 3517-4	1430	400/230	40	240	29,5/51,0	240	150	215
0,15/0,75	KG I2009-30/6	165/930	400	10/40	240	4,0/4,0	14/15	12	48
0,30/1,5	KG I2110-30/6	165/930	400	10/40	240	5,5/5,1	30/3	24	57
0,5/3,0	KG I2612-30/6	165/930	400	10/40	240	10,0/8,5	52	48	101
0,8/4,8	KG II2714-30/6	170/930	400	10/40	240	15,0/12,0	90	75	130
1,5/8,0	KG I3317-30/6	170/940	400	10/40	240	30,0/19,0	140	125	195
0,15/1,1	KG I2009-30/4	165/1400	400	10/40	240	4,0/4,0	14/16	15	48
0,30/2,2	KG I2110-30/4	165/1400	400	10/40	240	5,5/7,0	30	30	57
0,5/4,5	KG I2612-30/4	165/1400	400	10/40	240	10,0/11,0	52	55	101
0,8/7,5	KG II2714-30/4	170/1400	400	10/40	240	15,0/15,0	90	90	130
1,5/12,5	KG I3317-30/4	170/1430	400	10/40	240	30,0/8,0	140/180	135	195
0,16/0,75	KG I2009-24/6	200/930	400	25/50	300	3,0/3,4	18	12	48
0,33/1,5	KG I2110-24/6 KG II 2110-24/6	200/930	400	25/50	300	3,7/5,0	29	24	57
0,7/3,0	KG I2612-24/6	210/930	400	25/50	300	6,0/7,5	52	48	101
0,7/3,0	KG II2612-24/6	210/920	400	20/40	240	6,0/7,5	52	48	101
1,0/4,8	KG II2714-24/6 KG V 2714-24/6	200/940	400	25/50	300	11,0/12,0	100	75	130
1,7/8,0	KG I3317-24/6	200/920	400	25/50	300	15,0/18,0	140	125	195
3,0/13,0	KG3517-24/6	220/960	400	10/40	240	40,0/0,0	215	180	215
0,16/1,1	KG I2009-24/4	200/1400	400	25/50	300	3,0/3,5	16	15	48
0,33/2,2	KG I2110-24/4	200/1400	400	25/50	300	3,7/6,2	29	30	57
0,7/4,5	KG I2612-24/4	210/1400	400	25/50	300	6,0/9,5	52	55	101
1,0/7,5	KG II2714-24/4	200/1400	400	25/50	300	11,0/15,0	100	90	130
1,7/12,5	KG I3317-24/4	200/1430	400	25/50	300	15,0/3,0	140	135	195
1,9/11,5	KG3517-24/4	225/1400	400	10/25	120	30,0/5,0	170/180	'170	215
1,3/3,8	KG II112012-12/4	450/1320	400	10/40	240	11,5/8,8	46	50	75
0,19	EK 2110-24	230	400	40	1800	3,5	8	20	57